

## CLAIM AMENDMENTS

This listing of claims will replace all prior versions and listings in the application or in previous responses to office actions:

1. (currently amended) A nasal cannula assembly designed for contact with the nasolabial area of a patient's nose and comprising:

a hollow tubular member having an opening at each end, said tubular member having a central portion of sufficient length to span the width of an average patient's nostrils and end portions extending from each end of said central portion, said central portion having a pair of spaced, hollow extensions integral with and projecting therefrom said hollow extensions terminating in gas directing orifices and which hollow portion of said extensions communicate with said ~~hollow main body portion~~ hollow tubular member,

said central portion lying in a first plane with longitudinal axes symmetrical about a midpoint and forming an angle in said first plane less than 160 degrees,

each said hollow extension having a longitudinal axis projecting from said central portion at an acute angle from said first plane, said gas directing orifices of said hollow extensions having a longitudinal axis lying in a second plane essentially parallel to and displaced from said first plane,

said end portions of said central portion lying in essentially the first plane with longitudinal axis of said end portion essentially collinear with longitudinal axis of corresponding symmetrical half of said central portion.

2. (previously presented) A nasal cannula assembly as recited in claim 1, wherein said hollow extensions terminate in said gas directing orifices where thickness of material forming rim of said orifices is less than .006 inches.
3. (currently amended) A nasal cannula assembly as recited in claim 1, wherein the longitudinal axis of each said gas directing orifice is angled acutely in said second plane toward second said gas directing orifice such that the longitudinal axes of each said gas directing orifice intersect at an acute angle.

4. (previously presented) A nasal cannula assembly designed for contact with the nasalalabial area of a patient's nose and comprising at least one support tube having a 10% tensile modulus less than 200 psi.
5. (previously presented) A nasal cannula assembly as recited in claim 4 wherein said support tubes have a hardness between 40 and 75 Shore A.
6. (previously presented) A nasal cannula as recited in claim 4 wherein said support tubes have a compression set less than 45% at 23 degrees C per ASTM D-395.
7. (previously presented) A nasal cannula assembly as recited in claim 4 wherein said support tubes have a brittle temperature less than -40 degrees C per ASTM D-746.
8. (canceled)
9. (previously presented) A nasal cannula assembly as recited in claim 4 wherein said support tubes are manufactured from a polyvinyl chloride compound comprising at least a portion of polyvinyl chloride resin having an average molecular weight of at least about 100,000.
10. (previously presented) A nasal cannula assembly designed for contact with the nasalalabial area of a patient's nose and comprising at least main supply tube having a 10% tensile modulus less than 200 psi.
11. (previously presented) A nasal cannula assembly as recited in claim 10 wherein main supply tube has a hardness between 40 and 75 Shore A.
12. (previously presented) A nasal cannula as recited in claim 10 wherein main supply tube has a compression set less than 45% at 23 degrees C per ASTM D-395.
13. (previously presented) A nasal cannula assembly as recited in claim 10 wherein main supply tube has a brittle temperature less than -40 degrees C per ASTM D-746.
14. (canceled)
15. (previously presented) A nasal cannula assembly as recited in claim 10 wherein main supply tube is manufactured from a polyvinyl chloride compound comprising at least a portion of polyvinyl chloride resin having an average molecular weight of at least about 100,000.

16 – 19 (canceled)

20. (new) The nasal cannula assembly of claim 1 further comprising at least one support tube having a 10% tensile modulus less than 200 psi.
21. (new) A nasal cannula assembly as recited in claim 20 wherein said support tubes have a hardness between 40 and 75 Shore A.
22. (new) A nasal cannula as recited in claim 20 wherein said support tubes have a compression set less than 45% at 23 degrees C per ASTM D-395.
23. (new) A nasal cannula assembly as recited in claim 20 wherein said support tubes have a brittle temperature less than -40 degrees C per ASTM D-746.
24. (new) A nasal cannula assembly as recited in claim 20 wherein said support tubes are manufactured from a polyvinyl chloride compound comprising at least a portion of polyvinyl chloride resin having an average molecular weight of at least about 100,000.